

| ORDERING CODES V926 | | | | | | | | | |
|---------------------------------------------------------|---|---|------|----|----|----|-----|-----|---|
| VALVE CODES | P | V | .96H | 1 | D | 15 | .X. | | |
| Actuator type (1) | | | | | | | | | |
| Pneumatic actuator | P | | | | | | | | |
| Electric actuator | E | | | | | | | | |
| Group designation | | | | | | | | | |
| Globe valve, two way | | V | | | | | | | |
| Valve model | | | | | | | | | |
| V926H – Hygienic two way angle valve | | | .96H | | | | | | |
| V926A – Aseptic two way angle valve | | | .96A | | | | | | |
| Valve plug | | | | | | | | | |
| EQP (equal percentage) – Soft (High performance EPDM) | | | | 1 | | | | | |
| EQP (equal percentage) – Metal (AISI 316L / 1.4404) | | | | 3 | | | | | |
| PL (linear) – Soft (High performance EPDM) | | | | 6 | | | | | |
| PL (linear) – Metal (AISI 316L / 1.4404) | | | | 7 | | | | | |
| PT (on-off) – Soft (High performance EPDM) – V928A only | | | | 9 | | | | | |
| PT (on-off) – Metal (AISI 316L / 1.4404) – V928A only | | | | 10 | | | | | |
| Pipe connection | | | | | | | | | |
| Tri-clamp ferrules ASME BPE | | | | | D | | | | |
| Tube weld ASME BPE | | | | | DI | | | | |
| Size | | | | | | | | | |
| 1/2" | | | | | | 15 | | | |
| 3/4" | | | | | | 20 | | | |
| 1" | | | | | | 25 | | | |
| ... | | | | | | | | | |
| Actuator | | | | | | | | (1) | |
| Extras (3) | | | | | | | | | E |

| ACTUATOR CODES (pneumatic) | P. | 5 | R | P | 30 |
|-----------------------------------------------|----|---|---|---|----|
| Group designation | | | | | |
| Multi-spring, pneumatic linear actuator | P. | | | | |
| Actuator size | | | | | |
| 205 | | 1 | | | |
| 280 | | 3 | | | |
| 340A – From DN 15 to DN 50 | | 5 | | | |
| 340B – From DN 65 to DN 100 | | 6 | | | |
| 435A – From DN 15 to DN 50 | | 7 | | | |
| 435B – From DN 65 to DN 100 | | 8 | | | |
| Actuator type | | | | | |
| Direct action (air to close) | | | D | | |
| Reverse action (air to open) | | | R | | |
| Actuator Construction | | | | | |
| Steel construction (painted) – AdcaPure range | | | | P | |
| Stainless steel construction – AdcaPure range | | | | H | |
| Control signal | | | | | |
| 0,4 – 1,2 bar (6-18 psi) | | | | | 18 |
| 0,4 – 2 bar (6-30 psi) | | | | | 30 |
| 0,4 – 2,4 bar (6-35 psi) | | | | | 35 |

→ To be introduced on ".X.", if supplied in combination with the valve.

Example:

PV926H two way angle valve DN 50, tri-clamp ASME BPE complete with reverse action actuator signal 0,4 – 1,2 bar, size 340A steel:

Code: PV.96H1D50.5RP30

REMARKS:

(1) – Indicate actuator type.

(3) – To be used only when a non-standard combination valve is supplied.

Adcapure control valves are identified by a serial number on a nameplate, located on the valve and/or actuator yoke.

When ordering spares, always use that serial number. If the valve has non-standard extras the serial number also has an E (extras).