



Dist Check valve

Item No. :CW CV-D

Specifications:

Nominal pressure:PN1.6, 2.5, 4.0, 6.4MPa

Strength testing pressure:PT 2.4, 3.8, 6.0, 9.6MPa

Seat testing pressure(high pressure):1.8, 2.8, 4, 7.1MPa

Applicable media:

H71W-(16-64)C Water.Oil.Gas

H71W-(16-64)P Nitric acid

H71W-(16-64)R Acetic acid

Applicable temperature:-20~180° C

规格 参数	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
d	15	20	25	32	38	50	62	76	96
L	16	19	21.5	28	32	40	46	57	68
D	45	52.5	56.5	73	81	90	110	125	145
S	45	55	65	79	88.5	100	119	135	155

4	BONNET	CF8/CF8M	1
3	SPRING	304/316	1
2	DISC	CF8/CF8M	1
1	BODY	CF8/CF8M	1
NO.	NAME	MATERIAL	Q' TY


**Alfa com**  
 אלפא קום אספקה הנדסית בע"מ  
 Industrial Automation Products  
 www.alfacom.co.il  
 e-mail: info@alfacom.co.il