



SIZE	DN	L	H	E
1/2"	15	53	93	72
3/4"	20	55	100	72
1"	25	64	110	80
1 1/4"	32	72	138	100
1 1/2"	40	75	152	108
2"	50	90	180	130
2 1/2"	65	118	205	140
3"	80	137	226	140

Stainless Steel Female Gate Valve
SY11-(16-64)C、P、R

Specifications:

Nominal pressure:PN1.6,2.5,4.0,6.4MPa

Strength testing pressure:PT2.4,3.8,6.0,9.6MPa

Seat testing pressure(low pressure):0.6MPa

Applicable media:

Z15W-(16-64)C Water,Oil,Gas

Z15W-(16-64)P Nitric acid

Z15W-(16-64)R Acetic acid

Applicable temperature:-20~180°C

11	HANDLE	304	1
10	STEM NUT	CF8/CF8M	1
9	JUNK RING	304/316	1
8	V TYPE PACKING	PTFE	1
7	GASKET	304/316	1
6	LOCK NUT	304/316	1
5	VALVE COVER GASKET	PTFE	1
4	STEM	304/316	1
3	GATE	CF8/CF8M	1
2	BONNET	CF8/CF8M	1
1	BODY	CF8/CF8M	1
NO.	PART NAME	MATERIAL	Q' TY


Alfacom
 אלפא קום אספקה הנדסית בע"מ
 Industrial Automation Products
www.alfacom.co.il
 e-mail: info@alfacom.co.il