



- Features:
1. Temperature Range:-20 to 180 °C
 2. Full Port
 3. Investment Casting
 4. Blow-out Proof Stem
 5. Locking Device Handle (Option)
 6. PED 2014/68/EU
 7. Casting Approved AD2000-W0
 8. ISO5211 Mounting Pad
 9. Flange Dimension: DIN2501
 10. Inspection Testing: API598, EN12266-1

20	LUG WASHER	304	1
19	BOLT	304	1
18	SPRING WASHER	304	1
17	NUT	304	1
16	HANDLE NUT	304	1
15	HANDLE COVER	PLASTIC	1
14	HANDLE	304	1
13	WASHER	304	1
12	STEM NUT	304	1
11	BELLEVILLE WASHER	304	1
10	GLAND	304	1
9	PACKING	PTFE	1
8	O-RING	NBR/FPM	1
7	THRUST WASHER	PTFE	1
6	STEM	304/316	1
5	BALL	304/316	1
4	SEAT	PTFE/RPTFE	2
3	CAP	CF8/CF8M	1
2	SEAL	PTFE	1
1	BODY	CF8/CF8M	1
NO.	PART NAME	MATERIAL	Q' TY

SIZE	d	D1	D2	D3	N-M	L	W	H	S	ISO5211	W1	W2	K1	K2	
DN15	15	88	65	45	4-M12	37	140	80	9	F03/F04	36	42	6	6	PN40
DN20	20	98	75	58	4-M12	40	140	85	9	F03/F04	36	42	6	6	
DN25	25	105	85	68	4-M12	44	165	93	11	F04/F05	42	50	6	7	
DN32	32	130	100	78	4-M16	52	165	104	11	F04/F05	42	50	6	7	
DN40	38	148	110	88	4-M16	64	195	115	14	F05/F07	50	70	7	9	
DN50	50	165	125	102	4-M16	83	195	125	14	F05/F07	50	70	7	9	PN16
DN65	64	185	145	122	4-M16	107	260	145	17	F07/F10	70	102	9	11	
DN80	76	200	160	138	8-M16	120	260	152	17	F07/F10	70	102	9	11	
DN100	96	220	180	158	8-M16	145	300	180	17	F10		102		11	

