



2PC Ball Valve Light F/M

Model:2014

Features:

1. Pressure Rating:1000PSI/PN63
2. Working Temperature:-20° C to +180° C
3. Full Port
4. Investment Casting
5. Blow-out Proof Stem
6. Locking Device Handle (Option)
7. PED 2014/68/EU
8. Casting Approved AD2000-WO
9. Thread: ASME B1.20.1
BS21, DIN2999/259, ISO228-1, ISO7/1, JIS B 0203
10. Inspection Testing: API598, EN12516-2

13	HANDLE	304	1
12	STEM	304/316	1
11	STEM NUT	304	1
10	SPRING WASHER	304	1
9	GLAND NUT	304	1
8	STEM PACKING	PTFE	1
7	THRUST WASHER	PTFE	1
6	END SEAL	PTFE	1
5	CAP	CF8/CF8M	1
4	BALL	304/316	1
3	BALL SEAT	PTFE/RPTFE	2
2	BODY	CF8/CF8M	1
1	HANDLE COVER	PLASTIC	2
NO.	NAME	MATERIAL	Q' TY

1"	25	95	65
3/4"	20	80.5	65
1/2"	15	71	57
3/8"	12.5	59.5	48
1/4"	11.6	59	48
SIZE	D	L	W

