

FLOAT AND THERMOSTATIC STEAM TRAPS
FLT49TW
(Stainless steel ; 3" and 4" – DN 80 and DN 100)

DESCRIPTION

The ADCA FLT49TW is a series of high capacity float and thermostatic steam traps with integral air vent designed for modulating discharge of condensate, ensuring maximum system heat transfer.
Typical applications include unit heaters, heat exchangers, dryers, jacketed vessels and other applications where continuous discharge is essential and high flow capacities are involved.





MAIN FEATURES

Modulating discharge of condensate at steam temperature.
Unaffected by sudden or wide load and pressure variations.
No backing-up with condensate.
Excellent air discharge through its integrated air vent.
Flow direction can be easily changed by repositioning the body in relation to the mechanism and cover.

OPTIONS: Equalizing (vent) and drain connections.
HVV – Hand vent valve.
BDV – Blowdown valve.
AFZ – Anti-freeze device.
VB21M – Vacuum breaker.

USE: Saturated and superheated steam.

AVAILABLE MODELS: FLT49TW-4,5, FLT49TW-10, FLT49TW-21 and FLT49TW-32 – stainless steel.

SIZES: 3" and 4"; DN 80 and DN 100.

CONNECTIONS: Flanged EN 1092-1 PN 16 or PN 40.
Flanged ASME B16.5 Class 150 or 300.

INSTALLATION: Horizontal or vertical installation.

ΔPMX: FLT49TW-4,5 – 4,5 bar
FLT49TW-10 – 10 bar
FLT49TW-21 – 21 bar
FLT49TW-32 – 32 bar


CE MARKING – GROUP 2 (PED – EUROPEAN DIRECTIVE)		
PN 16	**PN 40**	**CATEGORY**
3" and 4" DN 80 and 100	–	1 (CE marked)
–	3" and 4" DN 80 and 100	2 (CE marked)


BODY LIMITING CONDITIONS				
FLANGED PN 16 *	**FLANGED PN 40 ***	**FLANGED CLASS 150 ****	**FLANGED CLASS 300 ****	**RELATED TEMPERATURE**
ALLOWABLE PRESSURE	**ALLOWABLE PRESSURE**	**ALLOWABLE PRESSURE**	**ALLOWABLE PRESSURE**	
15,1 bar	37,9 bar	13,3 bar	34,4 bar	100 ºC
12,7 bar	31,8 bar	11,1 bar	28,8 bar	200 ºC
11,9 bar	29,9 bar	10,2 bar	26,6 bar	250 ºC
11 bar	27,6 bar	9,7 bar	25,2 bar	300 ºC


PMO – Maximum operating pressure: 32 bar; TMO – Maximum operating temperature: 250 ºC.
* According to EN 1092-1:2018; ** According to EN 1759-1:2004.
Body limiting conditions PN 40 or below, depending on the type of connection adopted.

We reserve the right to change the design and material of this product without notice.

FLOW RATE CAPACITY (kg/h)													
MODEL	SIZE	DIFFERENTIAL PRESSURE (bar)											
		0,5	1	1,5	2	4,5	7	10	12	14	16	21	25	32
FLT49TW-4,5	3" and 4" – DN 80 and 100	15100	22000	28000	31000	45000	–	–	–	–	–	–	–	–
FLT49TW-10	3" and 4" – DN 80 and 100	7800	10000	12200	14200	20000	27500	32000	–	–	–	–	–	–
FLT49TW-21	3" and 4" – DN 80 and 100	3800	5400	6200	7200	10000	13800	16200	18000	19600	20100	22300	–	–
FLT49TW-32	3" and 4" – DN 80 and 100	3800	5400	6200	7200	10000	13800	16200	18000	19600	20100	22300	24000	25100









DIMENSIONS (mm)											
SIZE	PN 16								PN 40	CLASS 150	CLASS 300
	B	C	D	E	F	G	H *	WEIGHT (kg)	WEIGHT (kg)	WEIGHT (kg)	WEIGHT (kg)
3" – DN 80	339	113	273	161	350	677	3/8"	90,8	92,4	92	96
4" – DN 100	339	113	273	161	350	677	3/8"	90,3	93,8	94	102,5

* As standard, in versions with EN flanges, these connections are female threaded ISO 228. In versions with ASME flanges, these connections are female threaded NPT.

We reserve the right to change the design and material of this product without notice.

MATERIALS





Optional vacuum breaker (VB21M)

Optional hand vent valve (HVV)

Optional blowdown valve (BDV); Manual


Optional anti-freeze device (AFZ); Automatic

We reserve the right to change the design and material of this product without notice.


MATERIALS		
POS. No.	**DESIGNATION**	**MATERIAL**
1	Body	AISI 304 / 1.4301; AISI 316L / 1.4404
2	Cover	A351 CF8M / 1.4408
3	* Gasket	Stainless steel / Graphite
4	* Seat	A351 CF8 / 1.4308; A276-98B / 1.4057
5	* Gasket	Graphite
6	* Valve	AISI 316 / 1.4401; AISI 420 / 1.4021
7	* Lever	A351 CF8M / 1.4408
8	* Float	AISI 304 / 1.4301
9	* Automatic air vent	Stainless steel (bimetallic)
10	Stud	Stainless steel A2-70
10A	Nut	Stainless steel A2-70
11	Plug	AISI 316L / 1.4404
12	** Gasket	Copper; AISI 304 / 1.4301
41	Hand vent valve	AISI 303 / 1.4305; AISI 316L / 1.4404
51	Blowdown valve	AISI 303 / 1.4305; AISI 316L / 1.4404
61	Anti-freeze device	AISI 303 / 1.4305; AISI 316L / 1.4404
71	Vacuum breaker	AISI 303 / 1.4305
72	Adapter fitting	AISI 303 / 1.4305

* Available spare parts; ** Not applicable in NPT version.

FLOW DIRECTION



IH – Horizontal



IT – Vertical from top to bottom

We reserve the right to change the design and material of this product without notice.

ORDERING CODES FLT49TW								
MODEL	**A49T**	**2**	**V**	**XX**	**IH**	**L**	**80**	**E**
FLT49TW – A351 CF8M / 1.4408 stainless steel	**A49T**							
MAXIMUM ALLOWABLE DIFFERENTIAL PRESSURE (ΔPMX)								
4,5 bar		**2**						
10 bar		**3**						
21 bar		**4**						
32 bar		**5**						
AUTOMATIC AIR VENT								
Bimetallic air vent (standard)			**V**					
None			**X**					
COVER CONNECTIONS								
None				**XX**				
3/8" threaded connections on top and bottom, closed with plugs (mandatory if any options are considered)				**10**				
OPTIONS								
HVV, BDV, AFZ and VB21M have specific separated ordering codes, please refer to the appropriate documentation								
FLOW DIRECTION								
Horizontal					**IH**			
Vertical from top to bottom					**IT**			
PIPE CONNECTIONS								
Flanged EN 1092-1 PN 16						**L**		
Flanged EN 1092-1 PN 40						**N**		
Flanged ASME B16.5 Class 150						**U**		
Flanged ASME B16.5 Class 300						**V**		
SIZE								
3" or DN 80							**80**	
4" or DN 100							**100**	
SPECIAL CONSTRUCTION / ADDITIONAL OPTIONS								
A full description must to be provided and validated in case of a non-standard construction								**E**

We reserve the right to change the design and material of this product without notice.